

# TECHNICAL DATA SHEET RILSAN® PA11 ESY BLACK 7298

# **POLYAMIDE 11 POWDER**

RILSAN® fine powders are specialty polyamide powders obtained from renewable resources. RILSAN® ESY range is designed for coating metal parts using the electrostatic spraying process. They provide superior protection against wear, impact, corrosion, chemicals as well as graffiti. Please consult Arkema literature for application method and recommendations.

#### **DESIGNATION**

**PA11** 

#### MAIN APPLICATIONS

- · Water Fluid Coating Water Accessories
- · Oil And Gas Energy Pipe Coating
- Automotive/Truck Automotive Coating

#### **DELIVERY FORM**

Powder

## TRANSFORMATION PROCESSES

· Electrostatic spraying

#### **ADDITIVES**

Heat Stabilized

# **MECHANICAL PROPERTIES**

特性	DRY / COND VALUE*	UNIT	测试标准
Hardness, Shore D, 23°C (73°F)	- / 72		ISO 868
Hardness, Persoz, 23°C (73°F)	- / 270		ISO 1522
Abrasion resistance, Wheel CS 17, load 1 kg, 1000 cycles	- / 17	mg	ISO 9352

<sup>\*</sup>DRY: Dry As Molded (DAM) if pellet / Dry if powder. COND: Conditionned.

## THERMAL PROPERTIES

特性	价值	UNIT	测试标准
Melting temperature, 10°C/min	183-188	°C	ISO 11357-1/-3
Vicat softening temperature, 50N at 50°C/h	181	°C	ISO 306



# RILSAN® PA11 ESY BLACK 7298

# OTHER PROPERTIES

价值	UNIT	测试标准
0.20	kg/m²	Internal Arkema
≤ 1	%	ISO 62
30	μm	ISO 13320
9005		
Good adhesion after 2000 hours		ISO 9227
1.19	g/cm³	ISO 1183-1
0.44		ISO 1068
0.62		ISO 1068
20	%	ISO 13320
1	%	ISO 13320
	0.20 ≤ 1 30 9005 Good adhesion after 2000 hours 1.19 0.44 0.62	0.20 kg/m² ≤ 1 %  30 µm  9005  Good adhesion after 2000 hours  1.19 g/cm³  0.44  0.62 20 %

# 包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

• 20 kg / 44 lb bags

# 保质期

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

## SPECIAL CHARACTERISTICS

· Bio-based

